

**MICHAEL I. KROLL**

ATTORNEY AT LAW

171 STILLWELL LANE - SYOSSET, NEW YORK 11791

516-367-7777 800-367-7774\*

FAX 800-367-7704\* CAR PHONE 800-367-7779\*

\*TOLL FREE US & CANADA

International Phone/Fax 516-692-2787

Internet-http://invention.com E-Mail-patent@invention.com

Box PATENT APPLICATIONS

Assistant Commissioner of Patents  
Washington, D.C. 20231

**PATENTS, TRADEMARKS & COPYRIGHTS**

August 03, 1998  
(express mail)

Filing Patent Application

Re: US Patent Application

Title: **SAFETY DEVICE FOR AN ELECTRICAL OUTLET**

Inventor: **Paul Leroy Patterson Jr.**

Filing date: **08/03/98**

Honorable Commissioner of  
Patents and Trademarks:

Enclosed for filing please find the following:

1. Original Patent Specification
2. Copy of Drawing(s)
3. Original Declaration and Power of Attorney
4. Small Entity Declaration
5. Check for Filing Fee
6. Stamped self-addressed postcard
7. Information Disclosure document

Please indicate on enclosed postcard the application serial number and mail this pre-paid postcard to acknowledge receipt of this transmittal.

Thank you.

Very truly yours,

encl.  
MIK/ms

Michael I. Kroll

jc518 U.S. PTO  
09/128614  
08/03/98

## SAFETY DEVICE FOR AN ELECTRICAL OUTLET

### BACKGROUND OF THE INVENTION

#### Field of the Invention

The instant invention relates generally to electrical outlet guard covers and more specifically it relates to a safety device for an electrical outlet. The safety device for an electrical outlet will replace an existing cover plate of the electrical outlet, so as to cover the hazardous slots of the receptacle and yet appear very similar to the electrical outlet. An adult will have easy access to the receptacle, but it would be difficult for a child to gain access to the receptacle. This will help prevent the child from plugging in appliances that are dangerous to use, such as an electric knife, a can opener or a microwave oven, to name a few.

Description of the Prior Art

Numerous electrical outlet guard covers have been provided in prior art. For example, U.S. patents numbered 3,068,442 to Kubik et al.; 5,107,075 to Currier, Jr.; 5,563,373 to Doroslovac; 5,571,995 to Pierce and 5,675,126 to Halvorsen all are illustrative of such prior art. While these units may be suitable for the particular purpose to which they address, they would not be as suitable for the purposes of the present invention as heretofore described.

KUBIK, JOHN T.

KUBIK, STANLEY

SAFETY GUARD FOR WALL SOCKETS

U.S. Patent Number 3,068,442

A safety guard for electrical wall sockets comprising a box-like enclosure dimensioned to fit over the face plate of a wall socket of the type having a pair of vertically aligned sockets. The enclosure has a front wall extending parallel to and spaced outwardly from the face plate. The front wall has a pair of socket openings aligned with the sockets. A slide member is mounted for sliding vertical movement within the enclosure. The slide member has a pair of elongated arms extending vertically adjacent to the sides of the enclosure. The slide member has a pair of shorter arms spaced inwardly from the elongated arms. The space between the arms form a pair of elongated vertically directed slots. An upper bar is normally disposed in



CURRIER, JR., DONALD J.

SLIDABLE SAFETY COVER FOR ELECTRICAL OUTLETS

U.S. Patent Number 5,107,075

An improved slidable safety cover for use with electrical outlets is disclosed in which at least one slidable cover member is movably mounted on an apertured stationary frame overlaying an electrical outlet. The slidable cover member is movable between an open position at which access to underlaying electrical outlets is available through the slidable safety cover and a closed position at which access to the electrical outlets is blocked by the slidable cover member. Movement of the slidable cover member from the closed position to the open position requires release of a locking mechanism comprising at least one resilient finger latch member having a first end portion anchored to the stationary frame and a second end portion partially protruding through the slidable cover member. A finger latch opening is provided in the slidable cover member and is located distal from all sides of the safety cover slidable cover member.

DOROSLOVAC, SLOBODAN

SAFETY SHIELD FOR ELECTRICAL OUTLET

U.S. Patent Number 5,563,373

A safety device replaces the cover plate of a wall-mounted electrical outlet box having a pair of female receptacles for receiving a male plug. The safety device has a face plate, a back plate, a pair of shutters and a biasing means. The face plate has two large apertures in it, corresponding to the two female receptacles and exposing the receptacles when the face plate is positioned atop the outlet box and secured to it. The back plate has an inner surface and an outer surface and an aperture, which is shaped and positioned to correspond to the pair of female receptacles. When the front plate and back plate are mated, the front plate and the back plate are joined with the back face of the front plate, the inner surface of the back plate and a pair of parallel flanges on the back face defining a channel.

First and second shutters, corresponding to each of the large apertures on the face plate, cover the apertures. Each shutter is an imperforate shield member with an arm extending from each side and is positioned slidably within the channel, so as to obstruct the corresponding large aperture completely when in a first position and to provide access to a male plug through the large aperture when in a second position. The shutters are biased into the closed first position by a biasing means, preferably a pair of rubber bands.



HALVORSEN, GARY

OUTLET COVER

U.S. Patent Number 5,675,126

An outlet cover, for an electrical outlet, that is attachable over the electrical outlet itself or a face plate thereof. The outlet cover has a plate member with apertures for permitting access to sockets of the electrical outlet. Hinged doors swing to allow access to the sockets and to cover the sockets. A latch mechanism latches the doors shut over the sockets to eliminate an electrical shock hazard potential to children. The doors may be opened via an opening in a side surface of the outlet cover so positioned to be inconspicuous. The opening provides clearance for a prong, of an electrical plug, to be inserted therein to release the latch mechanism. Alternatively, a slot may be

provided in the side surface to accept a human nail, a pencil point, or a pin that may be used to release the latch, either along or in conjunction with a further mechanism for acting on the latch mechanism. An embodiment of the invention has the doors configured to lie flush with a face surface of the outlet cover.

09123614, 080398

PIERCE, DAVID B.

LOCKING SAFETY COVER FOR ELECTRICAL OUTLETS

U.S. Patent Number 5,571,995

A safety cover for electrical outlets includes a center locking block which is attached to an electrical outlet by a screw, and which has grooves to receive elongate members integral with individual receptacle covers. Matching cross-sectional shapes of the grooves and members fit closely so that elongate members are retained in the grooves. A flexible latching arm on the front of a receptacle cover engages the locking block to latch the cover in place. The latching arm is pressed aside with a fingertip to permit removal of the receptacle cover. One of the covers has prongs which engage openings in the receptacle to prevent the safety cover assembly from being rotated around the mounting screw.

SUMMARY OF THE INVENTION

A primary object of the present invention is to provide a safety device for an electrical outlet that will overcome the shortcomings of the prior art devices.

Another object is to provide a safety device for an electrical outlet that will replace an existing cover plate of the electrical outlet, so as to cover the hazardous slots of the receptacle and yet appear very similar to the electrical outlet.

An additional object is to provide a safety device for an electrical outlet in which an adult will have easy access to the receptacle, but would be difficult for a child to gain access to the receptacle, so as to help prevent the child from plugging in appliances that are dangerous to use, such as an electric knife, a can opener or a microwave oven, to name a few.

043034 003333  
A further object is to provide a safety device for an electrical outlet that is simple and easy to use.

A still further object is to provide a safety device for an electrical outlet that is economical in cost to manufacture.

Further objects of the invention will appear as the description proceeds.

To the accomplishment of the above and related objects, this invention may be embodied in the form illustrated in the accompanying drawings, attention being called to the fact, however, that the drawings are illustrative only, and that changes may be made in the specific construction illustrated and described within the scope of the appended claims.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

Various other objects, features and attendant advantages of the present invention will become more fully appreciated as the same becomes better understood when considered in conjunction with the accompanying drawings, in which like reference characters designate the same or similar parts throughout the several views, and wherein;

FIGURE 1 is an exploded front perspective view of the present invention ready to be installed over a receptacle in an electrical outlet.

FIGURE 2 is a front elevational view of the front cover plate taken in the direction of arrow 2 in Figure 1.

FIGURE 3 is a rear elevational view of the front cover plate taken in the direction of arrow 3 in Figure 1.

FIGURE 4 is a side elevational view of the front cover plate taken in the direction of arrow 4 in Figure 1.

FIGURE 5 is a front perspective view of the front cover plate.

FIGURE 6 is a front elevational view of the shields taken in the direction of arrow 6 in Figure 1.

FIGURE 7 is a rear elevational view of the two shields taken in the direction of arrow 7 in Figure 1.

FIGURE 8 is a side elevational view of the two shields taken in the direction of arrow 8 in Figure 1.

FIGURE 9 is a front perspective view of the two shields.

0912264 000390  
05E030 498760

FIGURE 10 is a front elevational view of the back cover plate taken in the direction of arrow 10 in Figure 1.

FIGURE 11 is a rear elevational view of the back cover plate taken in the direction of arrow 11 in Figure 1.

FIGURE 12 is a side elevational view of the back cover plate taken in the direction of arrow 12 in Figure 1.

FIGURE 13 is a front perspective view of the back cover plate.

Similar reference characters denote corresponding features consistently throughout the attached drawings.



DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Turning now descriptively to the drawings, in which similar reference characters denote similar elements throughout the several views, Figures 1 through 13 illustrate the present invention being a safety device 14. With regard to the reference numerals used, the following numbering is used throughout the various drawing figures.

14     safety device

16     electrical outlet

18     outlet box of 16 in 20

20     wall

22 receptacle of 16 in 18

24 upper socket of 22

26 lower socket of 22

28 central threaded opening in 22

30 cover plate screw

32 back cover plate of 14

34 upper aperture in 32

36 lower aperture in 32



00120044.000390

- 54 lower aperture in 50
- 56 central hole in 50
- 58 mating elements of 14
- 60 upper shield engaging facility of 14
- 62 lower shield engaging facility of 14
- 64 shields locking components
- 66 shields releasing elements
- 68 shields retaining structures

70 T-shaped slide panel for 40, 42

72 tab of 70

74 main flat body of 70

76 leg of 70

78 H-shaped cross member of 44

80 guide rail of 44

82 stud of 48

84 spring of 48



09120014-000390  
050000-100000

- 102 vertical slot in 50
- 104 hook end of 64 on 76
- 106 raised protrusion of 64 on 90
- 108 L-shaped tab of 66
- 110 first U-shaped tab of 68
- 112 second U-shaped tap of 68
- 114 horizontal depression in 40 of 68
- 116 horizontal depression in 42 of 68

The safety device 14 is for an electrical outlet 16 of the type that includes an outlet box 18 in a wall 20 for maintaining a receptacle 22 having vertically aligned dual sockets 24, 26 and a central threaded opening 28 between the sockets 24, 26 for receiving a cover plate screw 30. The safety device 14 comprises a back cover plate 32, having a pair of vertically aligned apertures 34, 36 therethrough with a central hole 38 between the apertures 34, 36. The apertures 34, 36 are shaped and positioned to correspond to the dual sockets 24, 26. The central hole 38 is aligned with the central threaded opening 28 of the receptacle 22 in the outlet box 18, when the back cover plate 32 is positioned over the outlet box 18. A pair of shields 40, 42 are sized to obstruct the apertures 34, 36 in the back cover plate 32, to prevent access to the dual sockets 24, 26 of the receptacle 22.

A structure 44 on a front face 46 of the back cover plate 32 is for guiding the upper shield 40 to move upwardly away from the upper aperture 34 in the back cover plate 32



and the lower shield 42 to move downwardly away from the lower aperture 36 in the back cover plate 32. Components 48 are for biasing the shields 40, 42 on the front face 46 of the back cover plate 32, so as to normally position the shields 40, 42 to obstruct the apertures 34, 36 in the back cover plate 32. A front cover plate 50 has a pair of vertically aligned apertures 52, 54 therethrough with a central hole 56 between the apertures 52, 54. The apertures 52, 54 are shaped and positioned to correspond to the dual sockets 24, 26 while the central hole 56 is aligned with the central threaded opening 28 of the receptacle 22 in the outlet box 18. Elements 58 are for mating the front cover plate 50 to the back cover plate screw 32 over the shields 40, 42, so that the cover plate screw 30 can engage with the central threaded opening 28 in the receptacle 22, to hold the safety device 14 thereto.

A facility 60 is provided, for engaging the upper shield 40 through the upper aperture 52 in the front cover plate 50, so that the upper shield 40 can move upwardly away from the upper aperture 34 in the back cover plate 32, to

00120044 000300  
expose the upper socket 24 of the receptacle 22. A facility 62 is also provided, for engaging the lower shield 42 through the lower aperture 54 in the front cover plate 50, so that the lower shield 42 can move downwardly away from the lower aperture 36 in the back cover plate 32, to expose the lower socket 26 of the receptacle 22.

The safety device 14 for the electrical outlet 16 further includes components 64 on the front cover plate 50, for locking each of the shields 40, 42 in the normally obstructing positions. Elements 66 on the front cover plate 50 are for releasing each of the shields 40, 42 from the normally obstructing positions. Structures 68 on the front cover plate 50 are for retaining each of the shields 40, 42 away from the sockets 24, 26 of the receptacle 22, so that an electrical plug (not shown) can engage with each of the sockets 24, 26 of the receptacle 22. Each shield 40, 42 is a T-shaped slide panel 70, having a pair of outwardly extending tabs 72 and a main flat body 74 with a pair of integral parallel legs 76, in which each leg 76 extends from one tab 72 adjacent the main flat body 74.

The guiding structure 44 consists of an H-shaped cross member 78 integrally formed centrally on the front face 46 of the back cover plate 32. A pair of vertically spaced apart side guide rails 80 are integrally formed on the front face 46 of the back cover plate 32 on opposite sides of the H-shaped cross member 78. The biasing components 48 include two studs 82 integrally formed on the front face 46 of the back cover plate 32. Four springs 84 are provided. Two springs 84 are connected between the upper shield 40 and the two studs 82, while other two springs 84 are connected between the lower shield 42 and the two studs 82.

The mating elements 58 are four small sockets 86 integrally formed on the front face 46 of the back cover plate 32 at the corners thereof. Four locking tabs 88 are integrally formed on a rear face 90 of the front cover plate 50 at the corners thereof, so that the locking tabs 88 can engage with the small sockets 86.

The upper shield engaging facility 60 includes the upper shield 40 having three depressions 92 in a front face

94 thereof simulating a hot slot, neutral slot and ground slot of the upper socket 24 of the receptacle 22, for engagement by the hot blade, neutral blade and ground prong of an electrical plug. The front cover plate 50 has three vertical slots 96 extending upwardly from the upper aperture 52 and in alignment with the three depressions 92 in the upper shield 40, to allow the electrical plug to raise the upper shield 40 to its uppermost position.

The lower shield engaging facility 62 consists of the lower shield 42 having three depressions 98 in a front face 100 thereof simulating a hot slot, neutral slot and ground slot of the lower socket 26 of the receptacle 22, for engagement by the hot blade, neutral blade and ground prong of an electrical plug. The front cover plate 50 has three vertical slots 102 extending downwardly from the lower aperture 54 and in alignment with the three depressions 98 in the lower shield 42, to allow the electrical plug to lower the lower shield 42 to its lowermost position.

The shields locking components 64 comprises the legs 76 of the shields 40, 42 having hook ends 104. Four

sets of two raised protrusions 106 are integrally formed on the rear face 90 of the front cover plate 50 above and below the apertures 52, 54 which engages with the hook ends 104.

The shields releasing structures 66 include the front cover plate 50 having four L-shaped tabs 108 cut therethrough above and below the apertures 52, 54. Each L-shaped tab 108 is in front of the two raised protrusions 106. When two of the L-shaped tabs 108 above and below the apertures 52, 54 are simultaneously manually depressed inwardly, the two hook ends 104 of the two legs 76 of one shield 40 or 42 will disengage from the raised protrusions 106. The shield 40 or 42 can be moved away from the respective aperture 52 or 54 in the front cover plate 50 and the respective aperture 34 or 36 in the back cover plate 32 by an electrical plug, to expose the respective sockets 24 or 26 of the receptacle 22.

The shields retaining structures 68 include the front cover plate 50 having two U-shaped tabs 110, 112 cut therethrough. The first U-shaped tab 110 is located

centrally adjacent a top edge and the second U-shaped tab 112 is located centrally adjacent a bottom edge. The upper shield 40 has a horizontal depression 114 in the front face 94 at a top end. The lower shield 42 has a horizontal depression 116 in the front face 100 at a bottom end. When the upper shield 40 is moved to its uppermost position, the first U-shaped tab 110 can be manually depressed into the horizontal depression 114 of the upper shield 40, to keep the upper shield 40 raised. When the lower shield 42 is moved to its lowermost position, the second U-shaped tab 112 can be manually depressed into the horizontal depression 116 of the lower shield 42, to keep the lower shield 42 lowered.

It will be understood that each of the elements described above, or two or more together may also find a useful application in other types of methods differing from the type described above.

While certain novel features of this invention have been shown and described are pointed out in the annexed claims, it is not intended to be limited to the details above, since it will be understood that various omissions, modifications, substitutions and changes in the forms and details of the device illustrated and in its operation can be made by those skilled in the art without departing in any way from the spirit of the present invention.

Without further analysis, the foregoing will so fully reveal the gist of the present invention that others can, by applying current knowledge, readily adapt it for various applications without omitting features that, from the standpoint of prior art, fairly constitute essential characteristics of the generic or specific aspects of this invention.

What is claimed is new and desired to be protected  
by Letters Patent is set forth in the appended claims:

1. A safety device for an electrical outlet of the type including an outlet box in a wall for maintaining a receptacle having vertically aligned dual sockets and a central threaded opening between the sockets for receiving a cover plate screw, said safety device comprising:
  - a) a back cover plate having a pair of vertically aligned apertures therethrough with a central hole between said apertures, said apertures being shaped and positioned to correspond to the dual sockets, while said central hole aligned with the central threaded opening of the receptacle in the outlet box, when said back cover plate is positioned over the outlet box;
  - b) a pair of shields sized to obstruct said apertures in said back cover plate, to prevent access to the dual sockets of the receptacle;



- 09120014 000320
- c) means on a front face of said back cover plate for guiding said upper shield to move upwardly away from said upper aperture in said back cover plate, and said lower shield to move downwardly away from said lower aperture in said back cover plate;
  - d) means for biasing said shields on said front face of said back cover plate, so as to normally position said shields to obstruct said apertures in said back cover plate;
  - e) a front cover plate having a pair of vertically aligned apertures therethrough with a central hole between said apertures, said apertures being shaped and positioned to correspond to the dual sockets, while said central hole aligned with the central threaded opening of the receptacle in the outlet box;
  - f) means for mating said front cover plate to said back cover plate over said shields, so that the cover plate screw can engage with the central threaded opening in the receptacle to hold said safety device thereto;

- g) means for engaging said upper shield through said upper aperture in said front cover plate, so that said upper shield can move upwardly away from said upper aperture in said back cover plate to expose the upper socket of the receptacle; and
- h) means for engaging said lower shield through said lower aperture in said front cover plate, so that said lower shield can move downwardly away from said lower aperture in said back cover plate to expose the lower socket of the receptacle.

2. A safety device for an electrical outlet as recited in Claim 1, further including:

- a) means on said front cover plate for locking each of said shields in the normally obstructing positions;
- b) means on said front cover plate for releasing each of said shields from the normally obstructing positions; and



b) a pair of vertically spaced apart side guide rails integrally formed on said front face of said back cover plate on opposite sides of said H-shaped cross member.

5. A safety device for an electrical outlet as recited in Claim 1, wherein said biasing means includes:

a) two studs integrally formed on said front face of said back cover plate; and

b) four springs in which two said springs are connected between said upper shield and said two studs, while other two said springs are connected between said lower shield and said two studs.

6. A safety device for an electrical outlet as recited in Claim 1, wherein said mating means includes:

a) four small sockets integrally formed on said front face of said back cover plate at the corners thereof; and

b) four locking tabs integrally formed on a rear face of said front cover plate at the corners thereof, so that said locking tabs can engage with said small sockets.

7. A safety device for an electrical outlet as recited in Claim 1, wherein said upper shield engaging means includes:

a) said upper shield having three depressions in a front face thereof simulating a hot slot, neutral slot and ground slot of the upper socket of the receptacle, for engagement by the hot blade, neutral blade and ground prong of an electrical plug; and

b) said front cover plate having three vertical slots extending upwardly from said upper aperture and in alignment with said three depressions in said upper shield, to allow the electrical plug to raise said upper shield to its uppermost position.

8. A safety device for an electrical outlet as recited in claim 1, wherein said lower shield engaging means includes:
  - a) said lower shield having three depressions in a front face thereof simulating a hot slot, neutral slot and ground slot of the lower socket of the receptacle, for engagement by the hot blade, neutral blade and ground prong of an electrical plug; and
  - b) said front cover plate having three vertical slots extending downwardly from said lower aperture and in alignment with said three depressions in said lower shield to allow the electrical plug to lower said lower shield to its lowermost position.
9. A safety device for an electrical outlet as recited in Claim 3, wherein said shields locking means includes:
  - a) said legs of said shields having hook ends; and

b) four sets of two raised protrusions integrally formed on a rear face of said front cover plate above and below said apertures which engages with said hook ends.

10. A safety device for an electrical outlet as recited in Claim 9, wherein said shields releasing means includes said front cover plate having four L-shaped tabs cut therethrough above and below said apertures, whereby each said L-shaped tab is in front of said two raised protrusions, so that when two of said L-shaped tabs above and below said apertures are simultaneously manually depressed inwardly said two hook ends of said two legs of one said shield will disengage from said raised protrusions, so that said shield can be moved away from said respective aperture in said front cover plate and said respective aperture in said back cover plate by an electrical plug to expose the respective sockets of the receptacle.

11. A safety device for an electrical outlet as recited in Claim 9, wherein said shields retaining means includes:

- a) said front cover plate having two U-shaped tabs cut therethrough, in which said first U-shaped tab is located centrally adjacent a top edge and said second U-shaped tab is located centrally adjacent a bottom edge; and
- b) said upper shield having a horizontal depression in a front face at a top end and said lower shield having a horizontal depression in a front face at a bottom end, so that when said upper shield is moved to its uppermost position said first U-shaped tab can be manually depressed into said horizontal depression of said upper shield to keep said upper shield raised, and when said lower shield is moved to its lowermost position said second U-shaped tab can be manually depressed into said horizontal depression of said lower shield, to keep said lower shield lowered.



12. A safety device for an electrical outlet of the type including an outlet box in a wall for maintaining a receptacle having vertically aligned dual sockets and a central threaded opening between the sockets for receiving a cover plate screw, said safety device comprising:

a) a back cover plate having a pair of vertically aligned apertures therethrough with a central hole between said apertures, said apertures being shaped and positioned to correspond to the dual sockets, while said central hole aligned with the central threaded opening of the receptacle in the outlet box, when said back cover plate is positioned over the outlet box;

b) a pair of shields sized to obstruct said apertures in said back cover plate, to prevent access to the dual sockets of the receptacle;



- g) means for engaging said upper shield through said upper aperture in said front cover plate, so that said upper shield can move upwardly away from said upper aperture in said back cover plate to expose the upper socket of the receptacle;
- h) means for engaging said lower shield through said lower aperture in said front cover plate, so that said lower shield can move downwardly away from said lower aperture in said back cover plate to expose the lower socket of the receptacle;
- i) means on said front cover plate for locking each of said shields in the normally obstructing positions;
- j) means on said front cover plate for releasing each of said shields from the normally obstructing positions; and



b) a pair of vertically spaced apart side guide rails integrally formed on said front face of said back cover plate on opposite sides of said H-shaped cross member.

15. A safety device for an electrical outlet as recited in Claim 14, wherein said biasing means includes:

a) two studs integrally formed on said front face of said back cover plate; and

b) four springs in which two said springs are connected between said upper shield and said two studs, while other two said springs are connected between said lower shield and said two studs.

16. A safety device for an electrical outlet as recited in Claim 15, wherein said mating means includes:

a) four small sockets integrally formed on said front face of said back cover plate at the corners thereof; and

b) four locking tabs integrally formed on a rear face of said front cover plate at the corners thereof, so that said locking tabs can engage with said small sockets.

17. A safety device for an electrical outlet as recited in Claim 16, wherein said upper shield engaging means includes:

a) said upper shield having three depressions in a front face thereof simulating a hot slot, neutral slot and ground slot of the upper socket of the receptacle, for engagement by the hot blade, neutral blade and ground prong of an electrical plug; and

b) said front cover plate having three vertical slots extending upwardly from said upper aperture and in alignment with said three depressions in said upper shield, to allow the electrical plug to raise said upper shield to its uppermost position.

18. A safety device for an electrical outlet as recited in claim 17, wherein said lower shield engaging means includes:

a) said lower shield having three depressions in a front face thereof simulating a hot slot, neutral slot and ground slot of the lower socket of the receptacle, for engagement by the hot blade, neutral blade and ground prong of an electrical plug; and

b) said front cover plate having three vertical slots extending downwardly from said lower aperture and in alignment with said three depressions in said lower shield to allow the electrical plug to lower said lower shield to its lowermost position.

19. A safety device for an electrical outlet as recited in Claim 18, wherein said shields locking means includes:

a) said legs of said shields having hook ends;  
and

b) four sets of two raised protrusions integrally formed on a rear face of said front cover plate above and below said apertures which engages with said hook ends.

20. A safety device for an electrical outlet as recited in Claim 19, wherein said shields releasing means includes said front cover plate having four L-shaped tabs cut therethrough above and below said apertures, whereby each said L-shaped tab is in front of said two raised protrusions, so that when two of said L-shaped tabs above and below said apertures are simultaneously manually depressed inwardly said two hook ends of said two legs of one said shield will disengage from said raised protrusions, so that said shield can be moved away from said respective aperture in said front cover plate and said respective aperture in said back cover plate by an electrical plug to expose the respective sockets of the receptacle.



09430641 000300

21. A safety device for an electrical outlet as recited in Claim 20, wherein said shields retaining means includes:

- a) said front cover plate having two U-shaped tabs cut therethrough, in which said first U-shaped tab is located centrally adjacent a top edge and said second U-shaped tab is located centrally adjacent a bottom edge; and
- b) said upper shield having a horizontal depression in a front face at a top end and said lower shield having a horizontal depression in a front face at a bottom end, so that when said upper shield is moved to its uppermost position said first U-shaped tab can be manually depressed into said horizontal depression of said upper shield to keep said upper shield raised, and when said lower shield is moved to its lowermost position said second U-shaped tab can be manually depressed into said horizontal depression of said lower shield, to keep said lower shield lowered.

ABSTRACT OF THE DISCLOSURE

A safety device (14) for an electrical outlet (16) comprising a back cover plate (32) having a pair of vertically aligned apertures (34), (36) therethrough. A pair of shields (40), (42) are sized to obstruct the apertures (34), (36) in the back cover plate (32), to prevent access to dual sockets (24), (26) of a receptacle (22). A structure (44) on a front face (46) of the back cover plate (32) is for guiding the upper shield (40) to move upwardly away from the upper aperture (34) and the lower shield (42) to move downwardly away from the lower aperture (36) in the back cover plate (32). Components (48) are for biasing the shields (40), (42) on the front face (46) of the back cover plate (32). A front cover plate (50) has a pair of vertically aligned apertures (52), (54) therethrough. Elements (58) are for mating the front cover plate (50) to the back cover plate (32) cover the shields (40), (42). A facility (60) is for engaging the upper shield (40) through the upper aperture (52) in the front cover plate (50) and move it upwardly away from the upper aperture (34) in the back cover plate (32). A facility (62) is for engaging the lower shield (42) through the lower aperture (54) in the front cover plate (50) and move it downwardly away from the lower aperture (36) in the back cover plate (32).







FIG. 1




**FIG 2**




**FIG 3**



**FIG 4**




**FIG 5**



**FIG 6**






**FIG 7**




**FIG 9**





**FIG 11**





**FIG 13**

# DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I declare that:

My residence, post office address and citizenship are as stated next to my name. I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

## SAFETY DEVICE FOR AN ELECTRICAL OUTLET

the specification of which is attached hereto unless the following is checked:  
\_\_\_\_\_ was filed on \_\_\_\_\_ as United States Application Number or PCT International Application Number \_\_\_\_\_ and was amended on \_\_\_\_\_ (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT international application having a filing date before that of the application on which priority is claimed.  
Prior Foreign Application(s): **none**

I hereby claim the benefit under 35 U.S.C. 119(e) of any United States provisional application(s) listed: Application number: **none**; Filing date: **none**

I hereby claim the benefit under 35 U.S.C. 120 of any United States application(s), or 365 (c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. 112.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application: Application no. **none**; Filing date: **none**; Status-patented, pending, abandoned: **none**.

POWER OF ATTORNEY: As a named inventor I hereby appoint the following attorney to prosecute this application and transact all business in the Patent and Trademark Office connected therewith:

**Michael I. Kroll, Registration number: 26,755**

SEND CORRESPONDENCE TO:

**Michael I. Kroll, telephone no. 516-367-7777  
171 Stillwell Lane, Syosset, New York 11791**

-----  
Inventor Last name: **Patterson, Jr.** First name: **Paul** Middle name: **Leroy**  
201 Residence(City): **Camp Pendleton** State: **California** Citizenship: **USA**  
P.O. address: **ACU-5 R-1, Box 555161; Camp Pendleton, California 92055-5161**  
-----

Inventor Last name: **n/a** First name: Middle name:  
202 Residence(City): State: Citizenship:  
P.O. address:

-----  
Inventor Last name: **n/a** First name: Middle name:  
203 Residence(City): State: Citizenship:  
Post office address:  
-----

I further declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful statements may jeopardize the validity of the application or any patent issuing thereon.

Signature of Inventor 201: Paul L. Patterson

Date: 6/25/98



Applicant and Inventor: **Paul Leroy Patterson, Jr.**  
Serial or Patent No.: filed herewith  
Filed or Issued: filed herewith  
Title: **SAFETY DEVICE FOR AN ELECTRICAL OUTLET**

**VERIFIED STATEMENT (DECLARATION) CLAIMING SMALL ENTITY**

As a below named inventor, I hereby declare that I qualify as an independent inventor as defined in 37 CFR 1.9(c) for purposes of paying reduced fees under section 41(a) and (b) of Title 5, United States Code, to the Patent and Trademark Office with regard to the invention with the above reference title described in:

- ☒ (X) in the specification filed herewith  
☐ ( ) application serial no. , filed  
☐ ( ) patent no. , issued

I have not assigned, granted, conveyed or licensed and am under no obligation under contract or law to assign, grant, convey or license, any rights in the invention to any person who could not be classified as an independent inventor under 37 CFR 1.9(c) if that person had made the invention or to any concern which would not qualify as a small business concern under 37 CFR 1.9(d) or a nonprofit organization under 37 CFR 1.9(e).

Each person, concern or organization to which I have assigned, granted, conveyed, or licensed or am under an obligation under contract or law to assign, grant, convey, or license any rights in the invention is listed below: (x) no such person, concern or organization

- ☐ ( ) persons, concerns or organizations listed below:  
☐ ( ) individual ☐ ( ) small business concern ☐ ( ) nonprofit organization

I acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b))

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application, any patent issuing thereon, or any patent to which this verified statement is directed.

Filed by: **Michael I. Kroll**, attorney for applicant; **Registration # 26,755**  
171 Stillwell Lane; Syosset, New York 11791; tele # 516-367-7777

Signature of Inventor: Paul L. Patterson

Date: 6/25/98